

Certificate of constancy of performance

No. 0672-CPR-1191

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s) **Thermal insulation products for buildings or for building equipment and industrial installations
Factory made mineral wool (MW) products
according to annex 1, page 1**

placed on the market under the name or trade mark of **URSA Slovenija, d.o.o
Povhova ulica 2
8000 Novo mesto
Slovenia**

produced in the manufacturing plant(s) **URSA Slovenija, d.o.o. (factory U)
8000 Novo Mesto
Slovenia**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA of the standard(s) **EN 13162:2012+A1:2015 and EN 14303:2009+A1:2013**

under system **1**

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2021-05-17** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Stuttgart, 2024-07-09

Dr.-Ing. Ralf Beutel
Deputy Head of Certification Body



Annex 1

to the certificate of constancy of performance No. 0672-CPR-1191

Product ¹⁾	Fire classification EN 13501-1	Field of application of the classification of product			
		Thickness [mm]	Density range [kg/m ³]	Organic content [% w/w]	Facing ²⁾
AP	A1	any thickness	any density	≤ 5.6	–
AP/(*)	A1	any thickness	≤ 45	≤ 5.4	(*) ³⁾
AP/(*)	A1	any thickness	≤ 40	≤ 5.0	(*) ⁴⁾
APh	A1	any thickness	any density	≤ 5.6	–
APh/(*)	A1	any thickness	≤ 45	≤ 5.4	(*) ³⁾
APh/(*)	A1	any thickness	≤ 40	≤ 5.0	(*) ⁴⁾
UP	A1	any thickness	any density	≤ 5.6	–
UP/(*)	A1	any thickness	≤ 45	≤ 5.4	(*) ³⁾
UP/(*)	A1	any thickness	≤ 40	≤ 5.0	(*) ⁴⁾
UPh	A1	any thickness	any density	≤ 5.6	–
UPh/(*)	A1	any thickness	≤ 45	≤ 5.4	(*) ³⁾
UPh/(*)	A1	any thickness	≤ 40	≤ 5.0	(*) ⁴⁾
FP ⁵⁾	A2-s1,d0	60-180	60-80	≤ 9.0	–
FP Basic ⁵⁾	A2-s1,d0	60-180	60-80	≤ 9.0	–
FP Advance ⁵⁾	A2-s1,d0	60-180	60-80	≤ 9.0	–
HT ⁵⁾	A2-s1,d0	60-180	60-80	≤ 9.0	–

¹⁾ These products are also sold under the trademarks:
"URSA TERRA" and „URSA TectONIC“

²⁾ Group of facings (*)

Group (*)³⁾

One or two-sided glass-fleece facing 35 - 80 g/m²

Group (*)⁴⁾

One-sided aluminium composite-layer film facing ≤ 66 g/m²

One-sided glass-fabric facing ≤ 125 g/m²

Facings glued with the Hotmelt adhesive ≤ 7 g/m²

⁵⁾ For application on wood-based materials with a thickness ≥ 10 mm and with a density ≥ 472,50 kg/m³, also on end-use substrates of classes A1 or A2-s1,d0.



Stuttgart, 2024-07-09